

Features:

- Deep Penetration. Improved Productivity. Reduced process time. **Defend with MightySteam[®] made with SaniZap[®].**
- Higher Temperature. Moisture-free production of non-chemical steam. No organic residue from steam. **Clean without Contaminating.**
- Use in **sensitive spots** where chemicals *should not* accumulate, including pet-messes.
- Best energy efficiency with patented steam production.
- No boiler. **On-Off at will.**



Special Introductory Pricing For a Limited Time

Place your order with a 10% deposit and balance due at shipment

Main Technical Specifications

Volts	110V to 120V Single Phase. (50/60Hz)
Current/Power	~1 kW Nominal
Phase	Single Phase, 50/60Hz
Pressure	1 bar / 14.5psi absolute (0 bar relative to room).
Variable Steam Temperature	300 °C – 400 °C Adjustable by flow. Fine tuning valve included
Water Reservoir	~4 hours for one fully filled Shoulder Pack (standard RO water recommended).
Capacity	Shoulder Pack can hold up to 1 gallon (May be used with partial fill)
Steam Production	Rapid

- Main unit with Shoulder Pack Included
- Shoulder Pack has Li-Ion rechargeable battery pump. Charger is included
- All cords included
- Easy Plug and Play
- Accurate water flow setting with high sensitivity needle valve.
- New technology to reduce any residual condensation and water residue.
- Pure steam with envelope hot air drying combinatoric process.
- Patented product.
- Continuous jet-use beyond an hour is allowed if device use is within allowed specifications. Safety distance flexible spring feature.
- Safety against earth fault (ground fault) is provided.
- (cUL) Canada Electronics are Offered where Required.
- Velocity of steam stream and dryer ~10 m/s
- Steam Production within minutes
- Class 4 Indicator testing is offered
- For easy steam cleaning and decontamination of targeted areas. Small area use antimicrobial product.
- Easy No-Leak feature. Quickly disconnects from Shoulder Pack.

